



CUSTOMER SUPPORT BULLETIN

Telos Zephyr – Using Autodial to change your SPIDs

23 June, 2000

This bulletin explains the steps necessary to program an Autodial Stored Setup which, once activated, will change the SPIDs and Telco settings entered in the Zephyr. This feature is available in firmware version 2.70 and later. We refer to this as a “Site Setup”. This allows you to call up the special Site Setup using the Autodial menu when arriving on site, to configure the Zephyr’s Terminal Adaptor for that site. You can then use other stored Autodial Setups in the usual fashion to dial out from the site.

Follow the steps below to create a Site Setup:

1. Go to the Zephyr’s 7th Utility menu by pressing the <Util> Key 7 times.
2. Set the Zephyr’s “Telco” setting to the correct setting for the setup to be created and press the <Yes/+> key to confirm. This setting will be part of your new Site Setup even though you will not be explicitly entering this information.
3. Go to the Zephyr’s 4th Utility menu by pressing the <Util> key 4 times. Verify that the brackets are around the number to the right of “Store setup” as shown below. If not, move the brackets up using the <^> key.

```
Store Setup           [1]
Category             Name
>                   <
    <+/-> to Change
```

4. Using the <No/-> or <Yes/+> key scroll to an unused setup.
5. Move the cursor down to “Category” using the <Sel v> key. The brackets should be around the word “Name” as shown below.

```
Store Setup           1
Category             [Name]
>                   <
    <+/-> to Change
```

6. Press the <Yes/+> key once to show “Num 1”.

7. Move the cursor down to the third line from the top using the <Sel v> key. Enter the first SPID number for this site here. Press the <Yes/+> key to confirm entry. As usual, enter the SPID without any spaces or punctuation. Enter them exactly as they were given to you by the phone company. Do not add anything to your SPID.
8. Move the cursor up to "Category" using the <Sel ^> key. The brackets will be around the word "Num 1" as shown below.

```
Store Setup          1
Category            [Num 1]
>                  <
                   <+/-> to Change
```

9. Press the <Yes/+> key once to show "Num 2".
10. Move the cursor down to the third line from the top using the <Sel v> key. Enter the second SPID number for this site here. Press the <Yes/+> key to confirm entry. As usual, enter the SPID without any spaces or punctuation. Enter them exactly as they were given to you by the phone company. Do not add anything to your SPID.
11. Move the cursor up to "Category" using the <Sel ^> key. The brackets will be around the word "Num 2" as shown below.

```
Store Setup          1
Category            [Num 2]
>                  <
                   <+/-> to Change
```

12. Press the <No/-> key twice to show "Name".
13. Move the cursor down to the third line from the top using the <Sel v> key. Enter the character "*" followed by a name for the setup. Press the <Yes/+> key to confirm entry. We suggest using a format that clearly indicates that this is a Site Setup not a normal Autodial Setup. For instance, you could use Site-sitename.
14. You must follow these steps in order given above for this to work. First enter the SPIDs as Num 1 and Num 2 and only then enter the name. The first character of the name must be "*". Zephyr firmware version 2.70 or later is required for this function.

Thank you for your support of Telos Systems. For more information see our web site www.zephyr.com or email support@telos-systems.com, or europa@telos-systems.com.